

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 25_BNC-75-2-8/133_N

Rev.: E



Description

Straight panel cable jack, flange mount

Interface Standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance 75 Ω

Interface frequency max. 1 GHz

Mechanical Data

Centre contact crimped

Outer contact crimped

Weight 0.0168 kg

Environmental Data

Operating Temperature -65 °C to 165 °C

2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact

Outer contact

Body

Insulator

Crimp ferrule

Material

Copper Beryllium / Brass

Brass

Brass

PFA / PTFE

Copper

Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00071040

Catalogue drawing DCA-00008807

Assembly instruction DOC-0000179123

Ordering Information

Single package 25_BNC-75-2-8/133_NE

Additional Information

Suitable cables RG_179_B/U, ENVIROFLEX_179, RG_187_A/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG

RF Technology

9100 Herisau, Switzerland

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions